



Regolo

Lampada da soffitto o parete. Diffusore in vetro soffiato opale satinato. Montatura in metallo verniciato bianco ral 9016. **Versione LED equipaggiata con led smd e alimentatore elettronico incorporato.**


Ceiling or wall lamp. Diffuser made in blown satin opal glass. Frame made in white painted metal ral 9016. **LED version equipped with smd led and electronic driver included.**

Lampe à plafond ou à mur. Diffuseur en verre soufflé opale satiné. Monture réalisée en métal vernie blanc ral 9016. **Version LED équipée avec led smd et ballast électronique incorporé.**

Lámpara de techo o pared. Difusor de vidrio soplado opal satinado. Montadura de metal pintado blanco ral 9016. **Version LED suministrada con led smd y alimentador electrónico incluido.**

Decken- oder Wandleuchte. Diffusor aus geblasenem Opalglas, satiniert. Fassung aus weiß lackiertem Metall Ral 9016. **Ausführung LED zum led smd und integriert Versorgungsgerät elektronisch.**


Regolo 250



Colore vetro Glass color

Articolo Item	Colore vetro Glass color		W _{max}	Icona	LUMEN	Icona	LUMEN/W	Icona	
	OP	Codice Code							
E27 regolo 250		11131	1x46	E27	700	IP40	⊕	15	A
● Led regolo 250 led-W		15521	6,2	led	850	IP40	⊕	137	B
● Led regolo 250 led-N		15531	6,2	led	850	IP40	⊕	137	B
EL regolo 250 EL		19971	1x18	G24q-2	1200	IP40	⊕	67	A

Regolo 350



E27 regolo 350		11141	2x46	E27	1400	IP40	⊕	15	A
● Led regolo 350 led-W		15541	11,5	led	1560	IP40	⊕	136	B
● Led DM regolo 350 DM led-W		15561	11,5	led	1560	IP40	⊕	136	B
● Led EM regolo 350 EM led-W		14701	11,5	led	1560	IP40	⊕	136	B
● Led regolo 350 led-N		15551	11,5	led	1560	IP40	⊕	136	B
● Led DM regolo 350 DM led-N		15571	11,5	led	1560	IP40	⊕	136	B
● Led EM regolo 350 EM led-N		14711	11,5	led	1560	IP40	⊕	136	B
EL regolo 350 EL		19981	2x18	G24q-2	2400	IP40	⊕	67	A

Colore vetro Glass color

OP
Opale satinato *Satin opal*

Led Equipaggiata con led 3000K - *Equipped with led 3000K*

Led Equipaggiata con led 4000K - *Equipped with led 4000K*

Led DM **Led DM** Dimmerabile PUSH/DALI
Dimmable PUSH/DALI (info page10)

Led EM **Led EM** Emergenza (SA) 1h di serie – 3h a richiesta
Emergency 1h standard – 3h on request

● **Nuova versione New version**

